

Micro UPS - Technical Specifications

model		Micro 360	Micro 550	Micro 750	Micro 1200	Micro 2200
capacity		360 VA / 220 W	550 VA / 330 W	750 VA / 450 W	1200 VA / 720 W	2200 VA / 1320 W
input	voltage	230 VAC Nominal				
	frequency	50 Hz / 60 Hz (Auto)		50 / 60 Hz +- 3% (Auto)	50 Hz / 60 Hz (Auto)	
output	voltage	230 VAC ± 10 % in inverter mode		230VAC +- 5%	230 VAC ± 10 % in inverter mode	
	frequency	50 Hz or 60 Hz ± 0,1 Hz		50 / 60 Hz +-1 Hz	50 Hz or 60 Hz ± 0,1 Hz	
	wave form	step wave				
battery	type	lead acid battery				
	battery size	7 Ah		9 Ah	7 Ah	
	quantity	1	1	1	2	4
	recharge time	7 hours at 90 %			4 hours at 90 %	
transfer time		typical 4 ms				
back up time in minutes	at 120 W load	12 - 18		15 - 20	20 - 180	
Software inclusive		Yes	Yes	Yes	Yes	Yes
SafeWare for Wind. 98,2000, XP, NT, Novell Netware, UNIX,...						
control	microprocessor	Yes	Yes	Yes	Yes	Yes
Buck & Boost (AVR)		No	No	Yes	Yes	Yes
communication		Yes	Yes	Yes	Yes	Yes
LED Displays	on-line	Yes	Yes	Yes	Yes	Yes
	in battery mode	Yes	Yes	Yes	Yes	Yes
	load up status	No	No	No	Yes	Yes
	Battery exchange	Yes	Yes	No	Yes	Yes
	Over Load			Yes		
protection	Internet/Fax/Modem/ DSL protection	Yes	Yes	Yes	Yes	Yes
	Autom. Diagnosis test	Yes	Yes	Yes	Yes	Yes
	Autom.Voltage.Regul. (AVR)	No	No	Yes	Yes	Yes
	unattended shutdown of all major operating systems	Yes	Yes	Yes	Yes	Yes
	outlets	230 V-IEC 320	4	4	4	6
dimensions in mm (HxWxD)		89 x 178 x 328		98 x 135 x 320	200 x 180 x 380	200 x 180 x 510
weight in KG		4,5	4,5	7,5	13	25
Standards		CE, UL		CE	CE, UL	

changes without notice

Stand: April 2005

Distributor
www.adpos-ups.de